SECURE MAIL PROXY SYSTEM, METHOD OF MANAGING SECURITY, AND RECORDING MEDIUM

BACKGROUND OF THE INVENTION

5   1.   Field of the Invention:

The present invention relates to a secure mail proxy system and a method of managing security for ensuring the security of electronic-mail, and to a recording medium in which a program is recorded.

10   2.   Description of the Related Art:

As systems for ensuring the security of electronic-mail, mail clients are widely used that are equipped with security capabilities such as: S/MIME (Secure Multipurpose Internet Mail Extension; Developed by RSA

15   Data Security Inc.) for transmitting encrypted mail messages in MIME format; and PGP (Pretty Good Privacy; an encryption program developed by PGP Inc. in which the mail content is encrypted using a public key of the transmission partner and then transmitted).

20   One method typically used to realize effective functioning of security involves installing beforehand one's own secret key as well as the transmission partner's digital identification in the terminal that one is using.

25   However, systems of the prior art for ensuring the security of electronic-mail have the following problems:

The range of terminals that receive mail has
increased from PC (personal computer) terminals of the
prior art to terminals such as portable telephones,
portable information terminals, and FAX (facsimile), and
5   this range has further been augmented by terminals not
having mail clients equipped with security functions, and
as a result, mail security could not be ensured on the
Internet.

In addition, the incorporation of security
10   functions on the terminal side has been problematic in
portable telephones, which have quickly become popular,
and this weakness has been an important factor in
preventing the use of the portable telephones for
business.

15

SUMMARY OF THE INVENTION

The present invention was achieved in view of the
above-described problems, and has as an object the
provision of a system and method, as well as a recording
20   medium, that can ensure the security of electronic-mail
on the Internet regardless of whether security functions
are incorporated on the client side.

In the present invention for realizing the above-
described object, a proxy server is arranged between a
25   mail server and the Internet for carrying out processing
relating to security of electronic-mail. This proxy

2

server is provided with a means for encrypting and decrypting electronic-mail, attaching signatures, and detecting falsification, and thus can ensure security of electronic-mail on the Internet regardless of the type of mail server, mail client or user terminal that is used by the user and regardless of whether mail security functions are incorporated in the mail server, mail client, or user terminal.

In the present invention, a proxy server is arranged between a mail server and the Internet for carrying out processing relating to the security of electronic-mail. Ordinary-text mail that has not been encrypted or not bearing a signature is transmitted to a mail server from a mail client that is connected to a LAN, this mail server detects whether or not the address of this mail is in the LAN, and sends only mail having an address outside the LAN to a proxy server as ordinary text without alteration. The proxy server includes means for encrypting ordinary-text mail that has been received from a mail server such that only the mail recipient can decrypt the mail; and means for attaching the signature of the mail originator to the mail and transmitting the encrypted mail with attached signature to the Internet.

The proxy server further includes: means for, when encrypted mail with attached signature has been transmitted in by way of the Internet addressed to a mail

3

server, checking whether or not the mail has been
subjected to falsification, and if the mail has not been
subjected to falsification, decrypting the encrypted mail
to ordinary text and transmitting to the mail server; and
5   means for, if mail has been subjected to falsification,
rejecting the reception of the mail to prevent entry of
the mail into the LAN.

The user uses the mail client to request the mail
server for mail that has been received, and receives
10   ordinary text mail from the mail server.

The above and other objects, features, and
advantages of the present invention will become apparent
from the following description based on the accompanying
drawings which illustrate examples of preferred
15   embodiments of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing the system
configuration of the first embodiment of the present
20   invention.

Fig. 2 is a block diagram showing an example of the
construction of a proxy server in the first embodiment of
the present invention.

Fig. 3 is a flow chart for explaining operations
25   when sending mail from a mail client in the first
embodiment of the present invention.

4

Fig. 4 is a flow chart for explaining operations when encrypted mail with attached signature has been received from the Internet in the first embodiment of the present invention.

5   Fig. 5 is a schematic view of an example of combinations of electronic-mail addresses and secret keys that are stored in the secret key storage unit in the first embodiment of the present invention.

Fig. 6 is a schematic view of an example of
10   combinations of electronic-mail addresses and public keys that are stored in the public key storage unit in the first embodiment of the present invention.

Fig. 7 is a block diagram showing the system configuration of the second embodiment of the present
15   invention.

Fig. 8 is a block diagram showing the system configuration of the third embodiment of the present invention.

20   DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Next, regarding an embodiment of the present invention, a proxy server for carrying out processing relating to the security of electronic-mail is arranged between the Internet and a mail server on a LAN (Local
25   Area Network). This proxy server ensures the security of electronic-mail on the Internet regardless of the type of

mail server, mail client or user terminal that is used by
the user and regardless of whether security functions are
incorporated in the mail server, mail client, or user
terminal by performing encryption and decryption of
5   electronic-mail as well as by attaching signatures and
detecting falsification.

In Fig. 1, a user uses mail client 3 that is
connected to LAN 1 to transmit ordinary-text mail that
has not been encrypted or provided with a signature to
10   mail server 2.

Mail server 2 checks whether or not the address of
electronic-mail (hereinafter referred to as simply
"mail") is within LAN 1, and sends only mail addressed to
destinations outside LAN 1 to proxy server 4 as ordinary
15   text without alteration.

Proxy server 4 encrypts the ordinary-text mail that
is received from mail server 2 such that only the mail
recipient can decrypt the mail, attaches the signature of
the mail sender, and sends the encrypted mail with
20   attached signature to Internet 5.

When encrypted mail with attached signature
addressed to mail server 2 is transmitted in from
Internet 5, proxy server 4 checks whether or not the mail
has been falsified.

25   If the mail has not been falsified, proxy server 4
decrypts the encrypted mail, and after converting it to

ordinary-text mail, sends it to mail server 2.

If the mail has been subjected to falsification, proxy server 4 rejects the reception of the mail to prevent the entry of the falsified mail into LAN 1.

5   The user uses mail client 3 to request the mail that has been received at mail server 2 and receives the ordinary-text mail from mail server 2.

Next regarding a more detailed explanation of this embodiment with reference to the accompanying drawings, 10   Fig. 1 is a block diagram showing the system architecture of the secure mail proxy system of the first embodiment of the present invention. Referring to Fig. 1, the first embodiment of the present invention is provided with: LAN 1, which is a local area network such as Ethernet; mail 15   server 2, which is an information processor that is connected to LAN 1; mail client 3, which operates on a device such as a personal computer, portable telephone, portable information terminal, or FAX; proxy server, which is an information processor that intermediates 20   between mail server 2 and Internet 5; and Internet 5.

Fig. 2 is a block diagram showing an example of the construction of proxy server 4 in the first embodiment of the present invention. Referring now to Fig. 2, proxy server 4 includes data processor 41 that operates under 25   program control, and storage device 42 that stores information.

Storage device 42 is provided with secret key storage section 421 and public key storage section 422.

Secret key storage section 421 stores combinations of electronic-mail addresses (hereinafter referred to as simply "mail addresses") and corresponding secret keys. The secret keys are used when attaching a sender's signature to electronic-mail, and when decrypting encrypted mail that has been transmitted to a mail address in LAN 1.

Public key storage section 422 stores combinations of electronic-mail addresses and corresponding public keys. Public keys are used when encrypting electronic-mail such that the mail can be read only by the user of the electronic-mail address that is designated in the address of the electronic-mail, and when checking whether or not electronic-mail has been falsified.

Data processor 41 is provided with: mail encryption means 411, mail decryption means 412, mail signature attaching means 413, mail signature checking means 414, and data communication means 415.

Mail encryption means 411 obtains the public key that corresponds to the electronic-mail address of an electronic-mail destination from public key storage section 422, and encrypts ordinary-text mail using the public key.

Mail decryption means 412 obtains the secret key

that corresponds to the electronic-mail address of the electronic-mail destination from secret key storage section 421 and decrypts the encrypted electronic-mail using the secret key.

5   Mail signature attaching means 413 obtains the secret key that corresponds to the electronic-mail address of the electronic-mail originator from secret key storage section 421, calculates the electronic-mail message digest (hash value) and, after encrypting these

10   values with the secret key, attaches them to the electronic-mail as the sender's signature.

Mail signature checking means 414 obtains, from public key storage section 422, the public key that corresponds to the electronic-mail address of the

15   originator of received electronic-mail, uses the public key to decrypt the signature that is attached to the electronic-mail, and checks whether or not the electronic-mail has been falsified by comparing the values of the signature with the electronic-mail message

20   digest (hash values).

Data communication means 415 receives ordinary-text mail from mail server 2 and transmits encrypted mail with attached signature to Internet 5, and further, receives encrypted mail with attached signature from Internet 5

25   and transmits ordinary-text mail to mail server 2.

In the first embodiment of the present invention,

the processing and functions of mail encryption means 411, mail decryption means 412, mail signature attaching means 413, mail signature checking means 414, and data communication means 415 are realized by a program that is executed by data processor 41. In this case, the proxy server according to the present invention can be operated by reading the program from a recording medium (magnetic disk, magnetic tape, optical disk, or semiconductor memory) that stores the program to data processor 41 and then executing the program.

Referring now to Figs. 1 to 6, a detailed explanation is next presented regarding the operation of the first embodiment of the present invention.

Fig. 3 is a flow chart for explaining operations when sending electronic-mail from mail client 3 in the first embodiment of the present invention. Explanation will begin with the transmission of electronic-mail from mail client 3.

The user creates electronic-mail using mail client 3 and sends the mail to mail server 2 as ordinary text (Step A1).

Mail server 2 checks whether or not the destination of the mail transmitted from mail client 3 is within LAN 1 (Step A2), sends the ordinary-text mail to proxy server 4 if addressed to a destination outside LAN 1 (Step A3), and if addressed to a destination within LAN 1, sends the

electronic-mail as ordinary text without alteration to
mail server 2 that is connected to LAN 1 (Step A4).

Proxy server 4 receives the ordinary-text mail from
mail server 2 by means of data communication means 415,
and by means of mail encryption means 411, obtains the
public key that corresponds to the mail address of the
destination of the electronic-mail from public key
storage section 422, and encrypts the ordinary-text mail
using the public key (Step A5).

Fig. 6 schematically shows an example of
combinations of electronic-mail addresses and public keys
that are stored in public key storage section 422.

If the mail address of the mail destination is "u-
suzuki@abc.com", "111···001" is used as the corresponding
public key in encryption.

By means of mail signature attaching means 413,
proxy server 4 next obtains the secret key that
corresponds to the electronic-mail address of the mail
originator from secret key storage section 421,
calculates the message digest (hash values) of the
electronic-mail, and, after encrypting these values using
the secret key, attaches them as the signature of the
mail sender (Step A6).

Fig. 5 shows an example of the combinations of
electronic-mail addresses and secret keys that are stored
in secret key storage section 421. If the electronic-

mail address of the mail sender is "t-azuma@nec.co.jp",
"101···001" is used as the corresponding secret key in the
signature.

Finally, proxy server 4 sends the encrypted mail
5   with attached signature to Internet 5 by means of data
communication means 415 (Step A7).

Fig. 4 is a flow chart for explaining the operation
when receiving encrypted mail with attached signature
from Internet 5 in the first embodiment of the present
10 invention. The operations when receiving encrypted mail
with attached signature from Internet 5 are next
explained.

Proxy server 4 receives encrypted mail with
attached signature from Internet 5 by means of data
15 communication means 415 (Step B1).

By means of mail signature checking means 414,
proxy server 4 obtains the public key that corresponds to
the mail address of the mail originator from public key
storage section 422, decrypts the signature that is
20 attached to the electronic-mail using the public key
(Step B2), and detects whether or not the electronic-mail
has been falsified by comparing the values of the
signature and the electronic-mail message digest (hash
values) (Step B3).

25   In the example of Fig. 6, when the mail address of
the mail originator is "u-suzuki@abc.com", "111···001" is

used as the corresponding public key for decrypting the
signature.

If the electronic-mail has not been falsified,
proxy server 4 uses mail decryption means 412 to obtain
5   the secret key that corresponds to the mail address of
the electronic-mail destination and decrypts the
encrypted electronic-mail using the secret key (Step B4).

In the example shown in Fig. 5, if the mail address
of the mail recipient is "t-azuma@nec.co.jp", "101···001"
10   is used as the corresponding secret key in the decryption
of the encrypted message.

The message that has been decrypted to ordinary
text is then sent to mail server 2 in LAN 1 by data
communication means 415 (Step B5).

15   In a case in which the electronic-mail has been
falsified, however, proxy server 4 rejects the reception
of the mail to prevent the falsified mail from entering
LAN 1 (Step B6).

Mail server 2 receives the ordinary-text mail from
20   proxy server 4 (Step B7), and returns the ordinary-text
mail to mail client [3] when there is a request from mail
client 3 (Step B9).

The user uses mail client 3 to request mail server
2 for mail that has been received (Step B8), and receives
25   ordinary-text mail from mail server 2 (Step B10).

Explanation next regards another embodiment of the

present invention.

Fig. 7 is a block diagram showing the construction
of the second embodiment of the present invention.
Referring to Fig. 7, the second embodiment of the present
5   invention may use any one or all of, for example, public
line network 61, radio communication network 62, and CATV
network 63 as a means for connecting mail client 3 to LAN
1 rather than connecting mail client 3 directly to LAN 1
as in the above-described embodiment.

10   A dial-up connection form is one example in which
mail client 3 is connected to LAN 1 by way of public line
network 61 using an Internet connection service provider
(ISP).

As an example of connection to LAN 1 by way of
15   radio communication network 62, connection is realized
from a portable telephone by way of a portable telephone
dealer that offers an Internet connection service.

As an example of a connection to LAN 1 by way of
CATV (cable TV), connection is realized by way of a CATV
20   company that offers an Internet connection service.

Next, regarding the third embodiment of the present
invention, we refer to Fig. 8, which is a block diagram
showing the construction of the third embodiment of the
present invention. Referring to Fig. 8, the present
25   embodiment includes key management server 7 and directory
server 8, and proxy server 4 is not provided with private

key storage section 421 and public key storage section 422.

Key management server 7 is a server provided exclusively for managing combinations of electronic-mail addresses and secret keys as shown in Fig. 5, and directory server 8 is provided exclusively for managing combinations of electronic-mail addresses and public keys, as shown in Fig. 6.

In this embodiment, mail encryption means 411 and mail signature checking means 414 of proxy server 4 acquire public keys from directory server 8.

In addition, mail decryption means 412 and mail signature attaching means 413 acquire secret keys from key management server 7.

Other than the acquisition of public keys and secret keys from directory server 8 and key management server 7, respectively, the processing procedure of proxy server 4 in the third embodiment of the present invention is similar to the procedures shown in Fig. 3 and Fig. 4.

As described in the foregoing explanation, the following effects can be obtained by the present invention:

As the first effect, the present invention can ensure mail security on the Internet without incorporating special software or devices in a terminal that transmits and receives mail.

The effect of the present invention to ensure
security is particularly notable in systems that employ,
as mail client terminals, the portable telephones and
portable information terminals that have rapidly come

5   into wide use. The present invention is effective both
because of the great variety of devices to be treated and
because of the huge number of units already in use.

The invention is effective because processing that
is necessary for ensuring mail security in the present

10   invention is allotted not to user-side terminals, but
rather, to a proxy server that is arranged at the
connection point with the Internet. The effect of the
present invention is also notable because threats to
security are far less serious inside the point at which

15   an in-house LAN connects to the Internet than on the
Internet itself, and security functions can be
concentrated at the point of connection with the Internet.

The second effect of the present invention is a
great reduction in management costs for ensuring security.

20   This effect is particularly notable for a user that
employs a plurality of terminals because security need
not be established at each terminal.

The invention is effective because, in the present
invention, the management of secret keys and public keys

25   that are necessary for ensuring security is centralized
at the proxy server and security settings are not

required for each client.

It is to be understood, however, that although the characteristics and advantages of the present invention have been set forth in the foregoing description, the disclosure is illustrative only, and changes may be made in the arrangement of the parts within the scope of the appended claims.